

# Blokkade

Your property and access, our challenge

DRIVE-THROUGH PROTECTION



## Blokkade: discrete, but ram-proof

Looking for ram-proof fencing? But it should not hinder the open appearance of your property? Then choose Blokkade drive-through protection. With this discrete, only 60 cm high fencing you prevent burglary- and escape attempts by motor vehicles. You always decide yourself who enters or leaves your property.

### Alternative for guardrails

We once developed Blokkade for theft and vandalism high risk locations. Today we also apply this fencing where vehicles may cause damage to buildings or objects. Here they are an elegant alternative to guardrails.

### Options

Blokkade is available in two versions: Blokkade and Blokkade heavy. The difference lies in the anchoring method and the construction strength. We secure passages with sliding tubes, sliding gates or retractable bollards.

### Application

- car dealers
- caravan companies
- parking areas
- industrial sites



Security starts outside



# Blokkade

## TECHNICAL SPECIFICATIONS

Blokkade type	Blokkade		Blokkade zwaar	
Height	600		600	
<b>Top rail</b>				
Tubular profile	60,3 x 1,75		60,3 x 1,75	
<b>Posts</b>				
Tubular profile	89 x 2,5		89 x 4	
Centre-to-centre	1500		1500	
Ground anchoring	rammed		rammed and ca 50 kg concrete	
<b>Sliding tube</b>				
Passage	2900	3900	2900	3900
Sliding tube	42,4 x 3,2	42,4 x 3,2	42,4 x 3,2	42,4 x 3,2
Inner tube	-	-	31,8 x 2,6	31,8 x 2,6
Collapsible intermediate post	no	no	1 piece round 89,4 in soil pipe 100 x 100 x 4	2 piece round 89,4 in soil pipe 100 x 100 x 4
Sliding tube seal	2 toggles 2 padlocks	2 toggles 2 padlocks	2 toggles 2 padlocks	2 toggles 2 padlocks

Dimensions in ca. mm.

### Version

#### Construction

- posts: round tubular profile, steel
- top tube: round tubular profile, steel
- finish: black plastic cover

#### Surface treatment

- hot-dip galvanized
- hot-dip galvanized, then powder coated according to the Duplex-system

#### Standard colours

- RAL 6009 (pine green)
- RAL 6005 (moss green)
- RAL 9005 (black)

#### Passage

- sliding tube
- sliding tube with inner tube and collapsible intermediate posts (complete with a cover and soil pipe)
- sliding gate
- retractable bollards

### Assembly

#### Posts

- standard: driving depth of approx. 900 mm
- centre-to-centre distance 1500 mm
- option: pour with concrete (depending on the version and soil condition)

#### Beams

- through the posts

Industrieweg 187a  
NL-5683 CC Best  
PO Box 66  
NL-5680 AB Best

Tel.: +31 499 363 666  
Fax: +31 499 399 945  
info@bgfencing.com



www.bgfencing.com

